

Descriptions

Class-D digital amplifier is used in ITC EVAC system, with 2U case integrated with 1 independent PFC functions, power saving control module and DC24V interface. Power is selectable from 120W/240W/350W/500W, channel is selectable from signal/dual/four channels.


Features

- * Adopt modular design, convenient for user to choose the function according to different needs.
- * Use high-efficiency Class-D digital amplifier, lower down the power consumption.
- * 2U case, 1 channel.
- * With overload protection, short-circuit protection and automatic temperature control function.
- * Automatically detect the status of each channel and with LED indicator to display the working status of each channel.
- * Support power saving mode. The amplifier will enter into standby status with no signal input.

Specifications

Model	VA-P350
AC Power	
Voltage	~220V-240V 50/60Hz
Current	2A
DC Power	
DC Input	DC~24V, ±20%
Current	18A
Power	350W
Power consumption	425 W
Audio data	
Input way	385mV Balance
Frequency Response	40Hz-20KHz, ±3dB
Output	100V Constant Voltage
Degree of Distortion	≤ 1% (Rated Power THD), 1KHz
S/N Ratio	≤ 80dB
Working Tem	5°C ~ 40°C
Relative Humidity	<95%
Cooling way	Air-Cooled
Protect way	Delay, over heat, short circuit, overload
Dimension	484 x 478 x 88mm
Weigh	8.1Kg

Back Panel <<



Connectors

- | | |
|-----------------------------|-----------------------------------|
| ① DC24V Input | ⑤ CH1-4 100V speaker line outputs |
| ② CH1-4 DC fuse | ⑥ Earth line |
| ③ Fan | ⑦ Power switch |
| ④ CH1-4 Balanced line input | ⑧ Power cord |