



Features

- * Controller of video camera to integration with audio conference system.
- * Automatic turn on the spokesman into the screen through the projector.
- * Capacity of connection with 6 cameras.
- * Capacity of each camera of 128 presets (for ceiling mounted camera) and 62 presets (for wall mounted camera).
- * Easy and convenient set up and control through the English PC software.
- * Support versatile control protocol like Samsung, Pelco-D & Visca.
- * Support different communicate baud rate of 2,400, 4,800, 9,600 & 19,200 for high resolution picture.
- * Support different resolution screen of 800x600, 1024x768, 1280x1024.
- * With picture frozen feature during the camera rotation, so as to enjoy a comfortable picture shift.
- * Picture frozen time could be set up from PC software from 0 to 6 seconds.
- * Wide AC power input of 100V to 240V.
- * Hi-pot test of more than 3,500V to ensure electronic operation safety.
- * Secure earth line grounded on both circuit and the metal case.
- * Anti interference of static electricity up to 8,000V.

Specifications

Model	TS-0690
Description	Auto Video Tracking Controller
AC Power Supply	AC100-240V; 50~60Hz
Power Consumption	7W
Video Input	BNC x 6 Balanced input
CVBS Input	0.5V~1.5Vp-p
Input Impedance	75 Ω
Output Impedance	75 Ω
Video Output	One BNC, one RCA & one VGA
RCA & BNC Output	0.5V~1.5Vp-p
Video Bandwidth	8MHz
VGA Output	1280x1024, 60Hz
Dimension (WxDxH)	484x210x44mm
Weight	3Kg
Color	Black