



### T-4012 Descriptions

The T-4012 is a remote paging microphone with 4 zone capacity for T-4060MP and T-4120MP amplifiers only. They are linked by RJ45 port through CAT5 cable, max 6 microphones can be cascaded together for one amplifier.

The microphone is built-in a two & four tone chime selector, it is powered by amplifier at 24V DC. Maximum communication distance is 1km. There are four zone selector, all call, talk and chime push buttons, the 10 segments level meter is supplied to display the output level. Built-in microphone, chime and master volume control.

### T-4012 Features

- \* 4 zone remote paging microphone
- \* With zone, group zone and all zone paging capacity
- \* One amplifier capacity is 4 microphones
- \* The microphone was connected to the amplifier through CAT 5 cable
- \* The microphone is DC24V powered by the amplifier at max 1km distance
- \* Built-in pre announcement chime of 2 & 4 tone selector
- \* With microphone, chime & master volume control
- \* With 10 segments level meter

### Specifications

<b>Model</b>	T-4012
<b>Mic Type</b>	Condenser microphone
<b>Communication Mode</b>	Level control
<b>Capacity</b>	4 ZONE
<b>Output Level</b>	1V/600 $\Omega$
<b>Frequency Response</b>	80~18KHz (+1/-3dB )
<b>THD</b>	$\leq 1\%$
<b>Power Consumption</b>	10W
<b>Communication Distance</b>	1KM
<b>Power Supply</b>	DC 24V
<b>Dimension</b>	220 x 142.7 x 51.5mm
<b>Weight</b>	1.35Kg (Without Microphone)

### Rear Panel T-4012

