



Remote Paging Console

T-8000A



Features

- * The T-8000A remote paging console is connected with T-8000 through universal industrial standard CAT 5 for zone announcement or communication at a remote and different location from the control center.
- * Each controller provides four RJ45 ports for the remote paging console.
- * The CAT 5 wiring is not only featured of cost-effective, convenient layout, but also integration of RS 485 communication and audio transmission together.
- * Extra DC 24V power supply.
- * Eight zone selector with state indication.
- * Talk and all zone paging swift keys are provided.
- * 2 and 4 tones chimes with selector and off switch.
- * Volume controls are provided for chime and microphone.
- * Full indications includes individual zone, all zone, busy, paging, power, output level to provide a direct visualization.

Specifications

Model	T-8000A
MIC	Condenser Microphone
Frequency Response	50Hz~18KHz (± 2 dB)
S/N Ratio	Better than 75dB
THD	Less than 0.1% at 1KHz,
Signal Output	0.775V/600 Ω
Mic Input	5mV/600 Ω
Indication	Individual zone, all zone, busy, paging, power, output level indicators
Protection	DC+24V/2A, Revert fuse protection
Power Supply	DC 24V
Power Consumption	5W
Weight	2.22Kg
Dimensions	200 x 142.7 x 51.5mm