



Features

- * With new digital design.
- * With ring-shaped speech indicator light that can show the state of speech. Red light stands for speaking, green light stands for waiting for a speech.
- * The special designed microphone shield can eliminate the "poop-poop" low frequency sound even without using the windproof cotton cover.
- * The chairman is unrestricted by microphone modes and number of speakers.
- * The chairman unit has full-control priority and can be placed in any position of the loop. The units adopt hand-in-hand cascade connection mode, convenient for installation and maintenance.
- * The reelable condenser microphone pole and professional large heart-shaped condenser microphones core make the unit a high sensitivity and intelligibility of the speech.
- * The microphone has high and adjustable sensitivity.
- * The power of the units is supplied by system host at 24V safe voltage.
- * The units are connected by T-shaped 8-core cable.
- * With two groups of 3.5mm stereo sound output socket, can be used for record and earphone connection.
- * Built-in hi-fi speaker and volume control; with feedback inhibition function. The built-in hi-fi speaker will shut off automatically when the microphone is turned on.
- * With discussion/automatic video-tracking function.

Specifications

Model	TS-0602
Microphone Type	Heart shaped projection electrets microphone
Frequency Response	80Hz~16KHz
Mic Input Impedance	1K Ω
Sensitivity	-46 dBV/Pa
Max SPL	100dB(THD>3%)
S/N Ratio	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Power Consumption	2W
Earphone Load	8-32 Ω
Earphone Volume	40mW maximum
Earphone Jack	3.5mm mono jack
Standard	IEC60914
Connector	Built-in 1.8m aviation plug (8 core)
Hand-in-hand Extension Port	Provided
Power Supply Mode	DC24V supplied by the host
Color	Black
Weight	0.86kg
Mic Tube Length	460mm
Dimension(mm)	144(L) \times 128(W) \times 62(H)
Installation Way	Desktop