



## **Features**

- \* Fully digital audio technology, microphone adopt 48KHz sampling rate, the sound is clear and bright, higher than CD sound quality. Interior has DSP audio processing. There is no low-frequency sound.
- \* 7-inch touch screen, elegant appearance with UI interface;
- \* The heart-shaped directivity capacitive pick up with double color indicator light, it is turn to red color during speaking, with rotary knob plug microphone bar.
- \* with inner magnetic type speaker, headphone jack. support headset microphones and microphone bar to pickup.
- $\ensuremath{^{*}}$  Support text messages, tea application and HELP(HELP) function.
- \* With cough elimination function, it can request the representative to slow down (SLOW).
- \* Support timekeeping of speech (charged according to speech time).
- \* Can preset the language of each channel.
- \* 15 kinds of languages can be translated at the same time, it can be customized 31 or 63 kinds languages, it can be installed up to six interpreter unit between an interpreter.
- st 3 fast inputs channel can be preset, with corresponding shortcut keys (a / b / c).
- \* With input channel selection buttons, you can easily select language from all the input language channels.
- ${}^{\ast}$  3 fast outputs channel can be preset, there are corresponding shortcut keys (A / B / C).
- $^{st}$  With output channel selection buttons, you can easily select language from all the input language channels.
- \* Support lock between interpreters and preemption modes.
- \* Packed with high-end headphones.
- \* Can be equipped with power adapter TS-0221DC to achieve long-distance power supply.

## **Specifications**

Model	TS-0670HY
Microphone Type	Cardioids directivity electret
Directivity	80Hz~16KHz
MIC Input Impedance	1KΩ
Sensitivity	-46 dBV/Pa
SPL Maximum SPL	100dB (THD>3%)
S/N Ratio	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Maximum Power Consumption	7W
Earphone Load	>16Ω
Earphone Volume	Maximum 40mW
Earphone Jack	3.5mm Mono socket
Standard	IEC60914
Connector	With 1.8m unified 6-core aviation cable
Hand in Hand Extension Port	l pcs
Power Supply Mode	Host power supply DC36V or adaptor power supply
Color	Black
Simultaneous Interpretation	16, 32, 64 Channe (Default 16)
Display Screen	7-inch color touch screen
Weight	1.65Kg
Microphone Pole Height	460mm
Dimension(mm)	268(L)×160(W)×63(H)
Installation Mode	Desktop type

www.itctech.com.cn Page 1 of 1