



Features

- * Microphone uses 48 KHZ sampling rate, the sound quality is higher than CD, clear and bright. with DSP audio processing inside, there is no 'poop-poop low-frequency shock.
- * Support speech timer and timing speech function.
- * Delegate Unit can apply for speech, the chairman can approve the applicant.
- * Built in feedback suppressor, can effectively prevent the squeal.
- * Chairmen unit has voice control function, open microphone intelligently.
- * With 5 segment EQ regulating function, can adjust the sound quality according to the characteristics of the speaker's voice, until reach the perfect effect.
- * Chairman has priority function, can close all is to speak on behalf of the receiver.
- * With a 4.3 -inch true color capacitive touch screen interface, simple operation, Human use of the machine function.
- * Adopting 100m network transmission, realizing hand in hand cascade, it won't effect the sound quality even in long distance transmission.
- * Having two sets of 3.5 mm stereo output socket, it can use to record and connect the headset.
- * One 3.5mm input socket, which can be used as headphone input.
- * Support a vote, election, rating function, chairman unit can raise a vote, check-in. can realize data statistics even without computer.
- * Language channel is selectable, the factory defaults is 15 + 1, you can set 31 + 1 and 63 + 1.
- * Service application function: Participants can send "tea application", "paper and pen application" and "manual service application" to the background according to actual needs.

Specifications

Model	TS-0205A
Microphone Type	Heart-shaped directivity electret
Directivity	80Hz~16KHz
Mic Input Impedance	ΙΚΩ
Sensitivity	-46 dBV/Pa
Max SPL	125dB (THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Power Consumption	5W
Headset Load	>16Ω
Headset Volume	Max 40mW
Headset Interface	3.5mm Mono jack
Standards	IEC60914
Connector	With 1.8m Aviation 6 core
Power Supply Mode	Host supply power DC36V
Color	Gray
Voting Function	Five key election, three key vote
Simultaneous Interpretation	16,32,64 Channel (default 16)
Check-in Function	Touch key check-in
Display Screen	4.3 inch capacitive screen
Weight	lkg
Mi Bar Height	460mm
Dimension(L×W×H)	206×174.2×65.5mm
Installation Way	Desktop Type

www.itctech.com.cn Page 1 of 1