



## Description

The product use intelligent control technology, take intelligent terminal as application concept, adopt original guide rail design, one key operation can automatically complete starting, LCD screen up, elevation and other actions, beautiful desktop, space-saving as the purpose, easy to use. With anti-theft, anti-dust, beautify desktop and other function. Can be widely used in conference, office hotel, teaching studio and other occasion, to meet the customer systems development diversity, and office automation environment demand. It is one ideal assistant of your office and teaching.

## Features

- \* touch ultra-thin HD display and lifter integrated design, no exposed cable, no connection backplane, no exposed screws, ensure a nice overall appearance of touch display screen.
- \* Built in an elevating microphone, microphone up and down with automatic straightening function, when MIC bending, it will be automatically straightening when machine close, won't be damaged.
- \* Equipment use all-aluminum structure, high-quality aluminum with CNC carved processing, display frame and chassis are made of aluminum alloy, to make equipment refined, lightweight, beautiful.
- \* Equipment surface treatment is anodized, bright color.
- \* Equipment panel thickness of only 3mm, width of only 70mm, small footprint.
- \* Adopt imported steel wire, cooperated with high precision guide rail and linear bearing, AC geared motor as driving force, reduce noise to minimum.
- \* 15.6-inch ultra-thin LCD touch screen display, resolution up to 1920\*1080P, clear and bright display, adjustable backlight design, to prevent fatigue caused by too bright or too dark.
- \* Support HDMI and VGA two channel signal input, when there is only one signal input, the screen will automatically recognize this signal, when these two signal input at the same time, can be manually switched from panel key, when no signal input, the screen will automatically enter into power saving mode.
- \* The device can be centrally controlled through central control software, can be controlled by the host computer, one key can make all device in the room go up or down.
- \* Built-in loop-through output power outlet, can power supply to the terminal to reduce terminal power outlet wiring, make project site wiring more neat and beautiful.

## Specifications

Model	TS-F173MT
Touch Screen	support
Lifting Time	28S
Elevation Angle	0-30° Fully comply with ergonomic, without blocking view and face
Chassis Dimension	586×60×519mm
Panel Dimension	601×70×3mm
Lifter Window Size	434.5×21.5mm
Desktop Hole Size	586×60mm (suggest physical device with hole)
Panel Sink Size	601×70×3mm (L×W×T) (suggest physical device with hole)
Environmental Condition	-20℃~50℃, related humidity ≤70%
Screen Size	17.3"
Screen Ratio	16 : 9
Screen Resolution	1920×1080
Video Interface	VGA, HDMI
Backlight Type	WLED, 15K hours, with LED driver
Contrast	700 : 1
Brightness	300cd/m <sup>2</sup>
Viewing Angle	89/89/89/89 (Typ.)
Display Thickness	10mm
Power Supply	AC 220V 50-60/HZ
Loop Through Output Power	AC 220V 50-60/HZ
Power Consumption	>25W
Total Weight	12Kg