



Features

- * The microphone adopt 48KHZ sampling rate, higher than the CD sound quality, the voice is clear and bright. Internal DSP audio processing, there is no low frequency sound.
- * Support speech timer and timing speech function
- * Delegate unit can apply for speech, the chairman unit can approve the applicant speech
- * Internal feedback inhibition function, can effectively prevent the noise.
- * With voice control function, adjustable voice sensibility, Turn on and off intelligently.
- * 5 Section EQ regulating function, different sound effects can be adjusted according to the characteristics of the speaker's voice until to achieve perfect effect.
- * The chairman has the priority function, which can turn off the Microphone of delegate units during speech.
- * With 100M network transmission to realize hand in hand cascade, Sound quality will not have any effect in long distance transmission.
- * Support the voting, election, rating function. Chairman unit can set vote, check-in function. Can do data statistics without PC.
- * Can choose language of received channel. Default setting is 15+1, optional setting is 31+1, 63+1.

Specifications

Model	TS-0236A
Mic Type	Heart-shaped directional electret
Frequency Response	80Hz~16KHz
Mic Input Impedance	1K Ω
Sensibility	-46 dBV/Pa
SPL Max SPL	125dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Power Consumption	2W
Headphone Load	>16 Ω
Headphone Volume	Max 40mW
Headphone Interface	3.5mm monaural jack
Standard	IEC60914
Interface	With 1.8m airplane 6 cores
Hand In Hand Expansion Port	Provide
Power Supply Way	Controller power supply DC36V
Color	Black
Voting Function	Five keys for selection, three keys for voting
Simultaneous Interpretation	16, 32, 64 channels (default 16)
Check In Function	Touch key to check in
Display LED	OLED full view low power consumption display
Wight	0.6kg
Gooseneck Height	415mm
Dimensions(mm)	250(L) \times 55(W) \times 85(H) mm
Installation Method	Embed
Hole Size	206 \times 48 mm